電磁場二用偵測器

- Digital Dual Function AC Electric/Magnetic(Gauss) Meter
- Measuring frequency range 16Hz to 2Khz
- The Meter sets new standards for technical data
- Comparable performance features can only be found in high end prefessional measuring technology
- Magnetic fields penetrate walls almost without resistance and Electric fields discharge to ground. With the Meter both fields can be investigated.



Technical Data

Magnetic Field Range	2000 nana Tessla (20 milliGauss) - Resolution 1nT (0.01mG)
Electric Field Range	2000 Volts/meter ? Resolution 1V/m? ground cable included
Accuracy	±2% @ 50hz, 20 degrees Celcius, 45% relative Humidity
Frequency Response	Flat Frequency Response from 16HZ to 2000 HZ at -2db
Display	3.5 inch Digital LCD ? field type indicator
Dimensions	$7.4 \times 18.0 \times 3.2 \text{ cm}$
Weight	175 grams
Material of Case	FR4
Power Supply	9 Volt alkaline battery
Operating Time	24 – 36 hours according to the mode of operation

Features

Tone: Audio signal proportional to field strength

Battery Low: Battery low indicator, meter will auto-power off after 3 mins

Auto power off: Auto power-off after 40 min of continuous use

元翔五金行 電話:04-22615775 傳真:04-22621395

住址:台中市復興路二段 120 之 19 號 http://yuansum.myweb.hinet.net